

Commercial freestanding safe

Office Line

811-816



Cash: £10,000 / €15,000 **Valuables:** £100,000 / €150,000

- type tested and supervised security by ECB-S
- fire protection with all-round fire fold
- certified protection against burglary according to EN 1143-1
- double walled body and door
- solid 3-sided locking through 28mm Ø round bolts and additional round dog bolts on hinge side
- prepared for floor fixing with fixing material 1 centrally arranged drill hole on the bottom. On request, the Office-Line safes with resistance grade I and II can be supplied with drill holes in the back wall at an extra charge
- file depth, adjustable shelves
- included shelf is fully adjustable (additional available to order)
- extra plus: non-resettable emergency re-locking mechanism within the door mechanics



Version K "SecuSafe"

Resettable armoured high-security safe lock

- VdS tested, class 2
- ECB-S certified according to EN 1300 class B
- 10 levers, key retaining
- 50 million key differs
- extra security in the event of losing the key: immediately resettable to a new key!
- locking armature protrudes 25 mm
- supplied with 2 keys

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door HxW	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 811 K	41710 2	626 x641 x554	476 x498 x370	476 x498	142	87
OL 812 K	41730 0	816 x641 x554	666 x498 x370	666 x498	205	122
OL 814 K	41750 8	1096 x641 x554	946 x498 x370	946 x498	213	174
OL 814 K 300	41770 6	1096 x641 x554	946 x498 x370	946 x498	305	174
OL 816 K	41780 5	1486 x780 x554	1336 x638 x370	1336x638	310	315



Version E FP "SecuTronic"

Programmable electronic lock with fingerprint module

- ECB-S certified according to class B
- graphic display with 1 admin code, up to 9 user codes and up to 20 fingerprints
- timer functions and assignment of rights
- incl. 4 Mignon LR06 AA batteries
- locking armature protrudes 50 mm

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door HxW	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 811 EFP	41700 3	626 x641 x554	476 x498 x370	476 x498	142	87
OL 812 EFP	41720 1	816 x641 x554	666 x498 x370	666 x498	205	122
OL 814 EFP	41740 9	1096 x641 x554	946 x498 x370	946 x498	213	174
OL 814 EFP300	41760 7	1096 x641 x554	946 x498 x370	946 x498	305	174
OL 816 EFP	41790 4	1486 x780 x554	1336 x638 x370	1336x638	310	315