



Commercial freestanding safe

Office Line

821-826



Cash: £17,500 / €26,000 **Valuables:** £175,000 / €260,000

- type tested and supervised security by ECB-S
- fire protection with all-round fire fold
- certified protection against burglary according to EN 1143-1
- double walled body and door
- solid 3-sided locking through 28mm Ø round bolts and additional round dog bolts on hinge side
- prepared for floor fixing with fixing material 1 centrally arranged drill hole on the bottom.
On request, the Office-Line safes with resistance grade I and II can be supplied
- with drill holes in the back wall at an extra charge
- file depth, adjustable shelves
- included shelf is fully adjustable (additional available to order)
- extra plus: non-resettable emergency re-locking mechanism within the door mechanics



Version K "SecuSafe"

Resettable armoured high-security safe lock

- VdS tested, class 2
- ECB-S certified according to EN 1300 class B
- 10 levers, key retaining
- 50 million key differs
- extra security in the event of losing the key: immediately resettable to a new key!
- the locking armature protrudes 25 mm
- supplied with 2 keys

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 821 K	41800 0	626 x 641 x 554	476 x 498 x 370	476 x 498	205	87
OL 822 K	41820 8	816 x 641 x 554	666 x 498 x 370	666 x 498	205	122
OL 824 K	41840 6	1096 x 641 x 554	946 x 498 x 370	946 x 498	239	174
OL 826 K	41860 4	1486 x 780 x 554	1336 x 638 x 370	1336 x 638	336	315



Version E FP "SecuTronic"

Programmable electronic lock with fingerprint module

- ECB-S certified according to class B
- graphic display with 1 admin code, up to 9 user codes and up to 20 fingerprints
- timer functions and assignment of rights
- incl. 4 Mignon LR06 AA batteries
- locking armature protrudes 50 mm

Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door H x W	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 821 E FP	41810 9	626 x 641 x 554	476 x 498 x 370	476 x 498	205	87
OL 822 E FP	41830 7	816 x 641 x 554	666 x 498 x 370	666 x 498	205	122
OL 824 E FP	41850 5	1096 x 641 x 554	946 x 498 x 370	946 x 498	239	174
OL 826 E FP	41870 3	1486 x 780 x 554	1336 x 638 x 370	1336 x 638	336	315