

# Safety cabinet

## Office Line

### 801-806

Cash: £2,000 / €2,500    **Valuables:** £20,000 / €25,000

- security level B according to VDMA 24992 (As of May 1995)
- double walled body and door
- solid 3-sided locking through 28mm Ø round bolts and additional round dog bolts on hinge side
- prepared for floor fixing with fixing material, 1 centrally arranged drill hole on the bottom
- file depth, adjustable shelves
- included shelf is fully adjustable (additional available to order)
- paintwork: Light grey (RAL7035)



#### Version K "SecuSafe"

##### Resettable armoured high-security safe lock

- VdS tested, class 2
- ECB-S certified according to EN 1300 class B
- 10 levers, key retaining
- 50 million key differs
- extra security in the event of losing the key: immediately resettable to a new key!
- locking armature protrudes 25 mm
- supplied with 2 keys



Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door HxW	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 801 K	41590 0	626 x641 x554	476 x498 x370	476 x498	110	87
OL 802 K	41610 5	816 x641 x554	666 x498 x370	666 x498	126	122
OL 802 K 300	41660 0	816 x641 x554	666 x498 x370	666 x498	300	122
OL 804 K	41630 3	1096 x641 x554	946 x498 x370	946 x498	163	174
OL 804 K 300	41680 8	1096 x641 x554	946 x498 x370	946 x498	300	174
OL 806 K	41650 1	1486 x780 x554	1336 x638 x370	1336 x638	300	315



#### Version E FP "SecuTronic"

##### Programmable electronic lock with fingerprint module

- ECB-S certified according to class B
- graphic display with 1 admin code, up to 9 user codes and up to 20 fingerprints
- timer functions and assignment of rights
- incl. 4 Mignon LR06 AA batteries
- locking armature protrudes 50 mm



Art.-No.	EAN	Exterior H x W x D	Interior H x W x D	Door HxW	Weight	Volume
	40 03482...	mm	mm	Opening mm	kg	l
OL 801 EFP	41580 1	626 x641 x554	476 x498 x370	476 x498	110	87
OL 802 EFP	41600 6	816 x641 x554	666 x498 x370	666 x498	126	122
OL 802 EFP300	41670 9	816 x641 x554	666 x498 x370	666 x498	300	122
OL 804 EFP	41620 4	1096 x641 x554	946 x498 x370	946 x498	163	174
OL 804 EFP300	41690 7	1096 x641 x554	946 x498 x370	946 x498	300	174
OL 806 EFP	41640 2	1486 x780 x554	1336 x638 x370	1336 x638	300	315