



# Specification Sheet

## Burton Home Safe Size 1 E



CASH  
RATING

£6,000



JEWELLERY  
RATING

£60,000



FIRE RATING

30 Minute  
Fire protection for  
paper

### **Dimensions of Safe:**

All dims H x W x D

External dims: 300mm x 400mm x 300mm

Internal dims: 195mm x 300mm x 200mm

Usable depth when door is closed: 165mm

Handle on safe is 40mm extra onto dimensions.

Weight: 65kg

Volume (litres): 11.7L

Safe is right hand hinged and opens to 180 degrees. Door is removable when in the open position.

### **Characteristics of Safe:**

Internal power supply (PP3 9-volt battery)

Ps310 lock EN1300:2013 Class B and ECB.S

C10 fitted comes with external power override (PP3 9-volt battery). Lock uses 6-digit code.

1 admin code (main code).

8 user codes.

Time delay 1-99 minutes.

RAL 7016 satin paint finish.

Serial number on outside of safe bottom right hand front corner.

Certified by ECBS to EN1143-1.

AIS insurance approved, Secured by Design – police approved.

Warranty card enclosed in safe.

### **Locking Bolts:**

30mm thick door with 3-point locking bolts which are 23mm diameter. 1 on the top and 1 on the bottom 2 on the leading/opening edge of the door. Dog bolt/deadbolt on hinge side for protection even when hinges are cut or attacked.

### **Fixing Bolts:**

Safe has 2 fixing holes in the base of the safe and 1 in the rear all are 15mm diameter and comes with 3 fixing bolts 12mm in diameter and 140mm long. All fixing holes are covered by plastic caps. Rear fix holes are not drilled all the way through the rear of the safe.

### **Shelves:**

Safe supplied with 1 shelf and 4 plastic shelf brackets but only has one position for use. Shelf size 315mm x 160mm. Shelf position from internal base of safe is 105mm.

### **Plates:**

Hardplate covering the lock area

Lock mounting plate doubles as a relocker that is the lock is punched off it acts as a relocker by blocking the boltwork

No glass plate

### **Updates:**

Please note mid-January 2019 fixing bolts changed from expanding fixing to thunder bolts 2 x M12 x 150 this bolt needs a 10mm diameter hole and screw the bolt into the hole using a socket set or spanner.

Please note before mid-January 2019 PS300 was fitted with 1 manager 1 user.

Certification EN15659 LFS 30P became a feature in July 2019.