



Specification Sheet

Burton Home Safe Size 2 E



CASH
RATING

£6,000



JEWELLERY
RATING

£60,000



FIRE RATING

30 minute
fire protection for
paper



Dimensions of Safe:

All dims H x W x D

External dims: 300mm x 450mm x 400mm

Internal dims: 195mm x 350mm x 300mm

Usable depth when door is closed: 260mm

Weight: 87kg

Volume (litres): 20.4L

Safe is right hand hinged and opens to 180 degrees. Door is removable when in the open position.

Locking Bolts:

30mm thick door with 3 point locking bolts which are 23mm diameter. 1 on the top and 1 on the bottom 2 on the leading/opening edge of the door. Dog bolt/deadbolt on hinge side for protection even when hinges are cut or attacked.

Characteristics of Safe:

Internal power supply (9 volt battery)

Internal power supply (PP3 9-volt battery)

PS310 EN1300:2013 Class B and ECB.S C10 lock fitted c/w external power override (PP3 9-volt battery). Lock uses 6-digit code before mid-January 2019 see notes below.

1 admin code (main code)

8 user codes

Time delay 1-99 minutes

RAL 7016 satin paint finish

Fixings:

Safe has 2 fixing holes in the base of the safe and 1 in the rear all are 15mm diameter and come with 3 fixing bolts 12mm in diameter and 140mm long. All fixing holes are covered by plastic caps.

Rear fix holes are not drilled all the way though the rear of the safe.

Certification and Warranty:

Certified by ECBS to EN1143-1 Grade 0 and EN15659 LFS 30P

AIS insurance approved, secured by Design – police approved

Warranty card enclosed in safe

Shelves:

Safe supplied with 1 shelf and 4 shelf brackets but only has one position for use. Shelf size 365mm x 255mm. Shelf position from internal base of safe is 105mm. Safe brackets are plastic

Plates:

Hardplate covering the lock area

Lock mounting plate doubles as a relocker that if the lock is punched off it acts as a relocker by blocking the boltwork

No glass plate

Updates:

Please note mid-January 2019 fixing bolts changed from expanding fixing to thunder bolts 2 x M 12 x 150 this bolt needs a 10mm diameter hole and screw the bolt into the hole using a socket set or spanner.

Please note before mid-January 2019 PS300 was fitted with 1 manager 1 user.

Certification EN15659 LFS 30P became a feature in July 2019.