

## HS1050 SERIES **NEPTUNE**



THE PHOENIX NEPTUNE HS1050 SERIES is designed to provide extreme security protection for domestic and business use.

- SECURITY PROTECTION Tested to the prestigious European EN1143-1 Security standard. ECB.S Certified Grade I. Recommended insurance rating of £10,000 cash or £100,000 valuables\*.
- APPROVALS UK Police approved (Secured by Design scheme) and the Association of Insurance Surveyors (AiS).

VdS class I key lock.

- FIRE PROTECTION Tested to the European LFS 30P fire protection standard (EN15659 ECB.S Certified) giving 30 minutes fire protection for paper records. HS1056 – Tested to the European LFS 60P fire protection standard (EN15659 ECB.S Certified) giving 60 minutes fire protection for paper records.
  - KEY LOCKING Fitted with high security double bitted

- **ELECTRONIC LOCKING** Fitted with high security VdS class II electronic lock with dual control, master code & time delay.
- **FIXING** Ready prepared for floor fixing, with fixing bolts for concrete supplied.
- **CONSTRUCTION** 3 way 24mm diameter locking bolts, double wall construction with specially formulated concrete infill, anti-drill plates and re-locker protection, provide a safe of great strength.
- **COLOUR** Finished in a high quality scratch resistant Graphite Grey paint RAL7024.
- Suitable for storage of controlled drugs whose active ingredients exceed 500 grams.

MODEL NUMBER	EXTERNAL DIMENSIONS H x W x D	INTERNAL DIMENSIONS H x W x D	DOOR Swing / Handle Depth	WEIGHT	CAPACITY	SHELVES		FOOLSCAP LEVER ARCH FOLDER (H350xW80xD285mm) Total no.of file per unit	
HS1051K/E	340 x 500 x 345mm	262 x 424 x 216mm	475/40mm	104kg	24 Litres	1	0	0	0
HS1052K/E	440 x 500 x 432mm	362 x 424 x 302mm	475/40mm	141kg	46 Litres	1	5	5	0
HS1053K/E	900 x 440 x 430mm	822 x 364 x 300mm	415/40mm	230kg	90 Litres	2	8	8	8
HS1054K/E	840 x 650 x 550mm	765 x 574 x 420mm	626/40mm	320kg	184 Litres	2	14	14	14
HS1055K/E	1240 x 650 x 554mm	1163 x 574 x 424mm	626/40mm	452kg	283 Litres	2	21	21	21
HS1056K/E	1950 x 940 x 585mm	1760 x 800 x 392mm	613/40mm	658kg	553 Litres	4	50	50	40



\* Ratings are approximate only and may vary due to area conditions and location. Please check with your underwriter.