ForceGuard is a security cabinet suitable for the storage of a range of valuable bulk items



ForceGuard

BURGLARY-RESISTANT PROTECTION

Key Features

- Available in four sizes, from 200 to 800 litres, with double doors on models 2–4.
- Single-wall body and door constructed with 3mm solid steel. Doors have a total thickness of 52mm and open to 180°.
- Secured by three-way boltwork, locking at the top, bottom and side of the door. All bolts are chromeplated and 20mm in diameter.
- Doors also fitted with relocking device to give additional protection against attempted forced entry.
- Key lock (Class A), combination lock (Class B) or electronic lock (Class B) fitted as standard. All locks approved in accordance with the European EN 1300 standard.
- All models equipped with removable shelves designed to accommodate hanging files.
- Anchor points in the base allow the cabinet to be fixed to the floor.
- All cabinets have a light-grey, powder-coated finish, suitable for any office space (RAL 7035).









Chubbsafes' policy is one of continuous improvement. Specifications may be subject to alteration from time to time without prior notice

Product Specifications

	External (mm)			Internal (mm)								
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)	Volume (litres)	No. of doors	No. of shelves	Rows of hanging files	Capacity hanging files (m)
CHSL T1	1000	600	430	854	580	375	80	186	1	2	3	1.74
CHSL T2	1500	900	430	1354	880	375	150	447	2	3	4	3.52
CHSL T3	1900	900	430	1754	880	375	200	579	2	5	6	5.28
CHSL T4	1900	1220	430	1754	1200	375	238	790	2	5	6	7.20

Lock Options



Electronic Lock

ForceGuard can be fitted with a double-bitted key lock, a 3-wheel combination lock or a high-security electronic lock as the primary locking option.

All standard locks have been certified by leading standards agency, ECB•S (European Certification Board•Security Systems), in accordance with the European norm, EN 1300. The key lock

is approved Class A and the combination and electronic lock have a Class B certification.

The electronic lock accommodates 1 master code, 1 supervisor code and up to 7 user codes. It features a time delay function of up to 99 minutes, dual control and optional duress alarm.

A secondary lock can be fitted on request.

Internal Fittings



Shelf with provision for hanging files

All cabinets can be fitted with frames for hanging files. A rail fixed to the roof of the cabinet allows the attachment of an extra file frame and means the largest model can accommodate 7.2 metres of hanging files.



Authorised dealer



www.chubbsafes.com