



BURGCAM-BULLET-304

WLAN 3MP IR bullet camera for indoor and outdoor
2,8mm fix lens, 12VDC, IP-66

PRODUCT DESCRIPTION

► Application:

The WLAN cameras of the BURGcam series are small, unobtrusive and easy to operate. Hence they are ideal for use in private homes. The cameras can also be setup without a PC, e.g. by using a matching App. In case of a detected event, the camera will send a push notification to your smartphone/tablet. Video data can be exported to a micro SD card. Thanks to the removable sunshield and the integrated IR LEDs with up to 30 meter range, this camera is ideal for outdoor applications, even at night.

► Technical specifications:

Type	WLAN Bullet Camera
Sensor type	1/3" Progressive Scan CMOS
Max. Picture resolution (pixel)	3 MP (2048x1536)
Video codec	H.264, H.264H, H.264B, MJPEG
Max. frame rate (fps)	20 at 3 MP, 25 at 2 MP
Number of video streams	2 (1x Main, 1x Sub)
Lens mount	Intern
Iris control	DC
Lens type	Fix lens
Focal length	2,8 mm, F2.0
Angle of view (horizontal)	90°
Sensitivity (Lux)	0,1Lux/F2.0(color), 0Lux/F2.0 (IR on)
IR cut filter	ICR-IR-Cut filter
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	AGC, manual
Digital noise reduction (DNR)	3DNR

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Shutter (sec.)	1/3 - 1/100,000
S/N ratio (dB)	< 50 dB
White balance	AWB / manual
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	DWDR
Digital zoom	Yes
Mirroring (vertical)	Yes
Motion detection	Yes
Privacy zones	Yes, 4 zones
Region of Interest (ROI)	No
Tampering Alarm	Yes
Camera title	Yes
Tripwire (IVA)	No
Intrusion (IVA)	No
Scene change (tampering)	No
IVS Missing / Added	No
Video output	No
Audio detect (IVA)	No
Audio support	No
Audio in-/outputs	No
Alarm contacts I/O	0 / 0
Schedule	Yes
Management software support	Many VMS
Cloud service	Yes, BURG-WÄCHTER cloud
Max number of users	20
Supported protocols	HTTP,TCP,UDP, DHCP,SMTP,UPnP,NTP, IPv4, IPv6, RTSP
Supported software standards	ONVIF, CGI
Internal memory	Micro SD (optional), max. 128 GB
Video Content Analytics (VCA)	No
Ethernet connector	RJ-45, WLAN
WLAN	Wi-Fi (IEEE802.11b/g/n)
Ethernet standards	10/100Base-T
Max. range (clear view)	50 m
Classification	IP-67
Vandal-proof	No
Heater	No
Installation	Wall and ceiling mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Metal
Integrated IR-LEDs	Yes
IR distance (m. ca.)	max. 30

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

DORI max. (Detect-Observe-Recognize-Identify)	63m - 25m - 13m - 6m
Voltage	12 V DC
Max. Power consumption (watt)	5,5 IR on
Operating temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	70 x 165
Weight	430 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide, power supply
Specials	WLAN, WPS, P2P, Cloud capable
Installation	Via WLAN (WPS) + App (Smartphone or Tablet), LAN

► **Note:**

A power adapter, a removable sunshield and a bracket are included in the delivery. A micro SD-card, however, is not included.

► **Recommended Accessories**

SNCA-MK-4531	Adapter / Junction box for SNC-311FBIF
JB-500	SANTEC Junction Box for cameras for WB-HDH (WB-HDHW) & SANTEC cameras